

CLIXXO

Business IP Phone IPX 935



CLIXXO IPX 935

- 2.4" 240x320-pixel HD color and 4 Line display with back light.
- 2 SIP Accounts.
- 2*10/100M Ethernet ports, integrated POE.
- Support 9 programmable keys.
- Optima HD voice, Full-duplex speakerphone.
- Auto-provision, HTTP/HTTPS/TFTP/FTP.

Phone Features

- 2 SIP accounts, MWI(Line1)
- Call hold, Call waiting, Call forward, Call return; Call transfer (blind/busy/ask)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Black list, Hand-free indicator.
- Call history: dialed/received/missed
- Soft keys programmable, Supports PC control

Advanced Features

- 9 DSS programmable keys
- XML Phone Book search and input & output
- Enterprise phone book (800 entries)
- Personal Phonebook (300 entries)
- LDAP phone book

IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call pickup, Dial Plan, Call recording
- Anonymous call, Anonymous call rejection
- Network conference, Distinctive ring tone

Optional Feature

- IPv6, HTTPS web management, 802.1x, OPEN VPN

Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711 μ /A, G.726, G.729AB,iLBC
- VAD, CNG, AEC, AGC, Full-duplex

Security

- VLAN QoS (802.1pq), SRTP
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Encryption for configuration file
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode, LLDP, CDP
- L2TP VPN tunneling protocol

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode
- SRTP voice encryption (RFC3711)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- TFTP/DHCP/PPPoE client
- Telnet/HTTP/HTTPS server, DNS client, NAT/DHCP server

Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- Configuration: browser/phone/auto-provision
- Trace package and system log export
- TR069

Physical Features

- 2.4inch 320x240 color screen with back light
- 25 keys, including 5 programmable keys,
- 2 LEDs: 2* account lights, including MWI(L1)
- 1* RJ9 handset port
- 2xRJ45 10/100M Ethernet ports
- Power adapter: AC 100~240V input and DC 5V/1A output
- POE ,IEEE 802.3af,class 0(Option)
- Power consumption: 1.5W
- Net weight: 0.62kg
- Dimension: 180x157x33mm
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

Package Features

- Qty/CTN: 10 PCS
- N.W/CTN:
- G.W/CTN:
- Carton Meas:

Certifications



CLIXXO BROADBAND PRIVATE LIMITED

Address: B-16, Sector-67, Noida (U.P.) - 201301

Email: corporate@clixxo.com Tel: +91 120 2210100 Fax: +91 120 2975335